


BRIDGE CLAMP Quick release

213

Image not found or type unknown



secure clamping with special bridge

conforms to REACH guideline

- REACH according to --> Technology / Technical Information / REACH

DESIGN

- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Clamp wire: stainless steel 1.4310 = AISI 301 (INOX); Screw: stainless steel 1.4301 = AISI 304; Body: stainless steel 1.4016 = AISI 430

DELIVERY VARIANTS

- further diameters available on request

SUITABLE FOR HOSE

- AIRDUC®: 341 + 345 + 363; 350 (AS /FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC); PROTAPÉ®: 326 + 327 MEMORY; 330 (FOOD / AS BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321; 322 EC; 332 SE;
- CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC); TIMBERDUC®: 531 - 533 AS

On stock at the manufacturer, short delivery time with regular shipments

Hose ID (mm)

Article Nr.

60

213-0060-0000

70

213-0070-0000

75

213-0075-0000

80

213-0080-0000

90

213-0090-0000

100

213-0100-0000

110

213-0110-0000

115

213-0115-0000

120

213-0120-0000

125

213-0125-0000

130

213-0130-0000

140

213-0140-0000

150

213-0150-0000

Hose ID (mm)

160

175

180

200

Article Nr.

213-0160-0000

213-0175-0000

213-0180-0000

213-0200-0000

