



Clamp 212 EC Bridge Clamp (with bridge strip) for attaching external hoses



Clamping (via earth) of hoses

Clamping spiral and without damaging hose
secure clamping with special bridge

- easily and quickly fitted
- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

DESIGN

- Quality: W2; Clamp strip: stainless steel 1.4301 = AISI 304; Screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; Bridge: stainless steel 1.4301 = AISI 304 (INOX)
- in accordance with DIN 3017

DELIVERY VARIANTS

- further diameters available on request (MOQ)

SUITABLE FOR HOSE

- AIRDUC®: 341 + 345 + 363; 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC); TIMBERDUC®: 533 AS

On stock at the manufacturer, short delivery time with regular shipments

Hose DN (mm)	Band width (mm)	Clamping range (mm)	Article Nr.
38-45	9	32-55	212-0035-2878
50-55	9	45-65	212-0045-2878
60-65	9	55-75	212-0055-2878
70-75	9	65-85	212-0065-2878
80-85	9	75-95	212-0075-2878
90-95	9	85-105	212-0085-2878
100-105	9	95-115	212-0095-2878
110-115	9	105-125	212-0115-2878
120-127	9	115-135	212-0125-2878
130-135	9	125-145	212-0125-2878
140-145	9	135-155	212-0135-2878
150-155	9	145-165	212-0145-2878
160-165	9	155-175	212-0155-2878
190-195	9	185-205	212-0185-2878
200-205	9	195-215	212-0195-2878

Hose DN (mm)

250-255

350-355

Band width

10

10

(mm)**Article Nr.**

212-0245-2878

212-0345-2878

image not found or type unknown

image not found or type unknown

